

COSHH – Assessment Sheet

Company:	Date:
ServiceMaster Clean by Deeland Ltd	Jan 2025
Product:	Main Hazardous Constituent(s):
Select Polish	Naphtha (Petroleum)
	CAS No-64742-48-9
	n .
	Butane
	CAS No-106-97-8
	Propane
	CAS No 74-98-6
	Isobutane
	CAS No 75-28-5
	Reaction Mass of 5-Chloro-2-methyl-2H-
	Isothiazol-3 one and 2-methyl-2H-Isothianzol-
	3-one
	CAS No 55965-84-9
Where Used:	Risk Stated:
Furniture polish	H222-Extremely flammable aerosol
For professional use only	H229-Pressurised container. May bust if heated
	Those at Risk: Personnel working with the concentrate.
Hazard Form:	Risk Via:
Liquid, white aerosol	
Floral	Inhalation Yes
	Absorption through skin Yes
	Ingestion Yes
	Contact with eyes/skin Yes
Health Effect(s):	Exposure Limits:
Inhalation—High concentration of vapours	Butane—OEL TWA (1) 1450 mg/m3—600ppm
may induce headache, nausea and dizziness.	(2) 1810 mg/m3—750ppm
Skin—Repeated exposure may cause skin	Promono OEL TWA 1000
dryness and cracking.	Propane OEL TWA 1000ppm
Eyes—Causes eye irritation	Jackytone OEL TWA 1000mm
Ingestion—May cause slight irritation to	Isobutane OEL TWA 1000ppm
linings of the mouth, throat and	
gastrointestinal tract.	



Handling/Usage: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Do not eat, drink or smoke when using this product.

Personal Protective Equipment: Not required for normal use.

General Assessment: A silicone-based spray polish for furniture, tiles, marble stainless steel and most plastic and vinyl coated materials.

	The and viriyi coated materia	
Material:	Stainless Steel Cleaner	
Protective	Exposure Limits:	As above
Equipment:	Ventilation:	Not required for normal conditions of use.
	Respiratory Protection:	Not required for normal conditions of use.
	Eye Protection:	No specific eye protection required in normal use.
	Hand/Skin Protection:	Not required for normal conditions of use.
First Aid Methods:	Inhalation:	Remove person to fresh air and keep comfortable for breathing.
	Skin Contact:	Wash skin with plenty of water and take off
		contaminated clothing.
	Eye Contact:	Rinse cautiously with water for several minutes.
		Remove contact lenses, if present and easy to do.
		Continue rinsing. If eye irritation persists, get medical
		attention.
	Ingestion:	Do not induce vomiting. Rinse mouth, drink plenty of
		water. Get medical advice/attention.
Fire:	Extinguishing media:	Carbon dioxide, Dry powder, foam
	Special firefighting	Use water spray or fog for cooling of exposed
	procedures:	containers.
	Unusual fire &	Extremely flammable aerosol. Explosion risk in case
	explosion hazards:	of fire.
Storage:	Keep in original container, away from direct sunlight, heat sources and sources of	
	ignition. Do not expose to	temperatures exceeding 50C.
Transport:	UN 1950 Aerosols	
Spillage:	Collect spillage, soak up with inert solids, such as clay or diatomaceous earth as	
Waste	soon as possible. Product:	Disposal should be in accordance with regulations
disposal:	Container:	
uispusai:	Container:	Disposal should be in accordance with regulations. Do not pierce or burn after use.
	I .	Do not pierce of built after use.

Signed Originator: Andy Goodman Job Title: Business Operations Coordinator

Date Completed 06.01.25 Date for Revision: 06.01.26

Site assessment compiled for: Servicemaster Clean by Deeland Ltd